Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



9986 Hook-up/Lead - UL AWM Style 1061

For more Information please call

1-800-Belden1



General Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

Physical Characteristics (Overall)

AWG:



Total Number of Conductors:

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.010

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.035 in.

Mechanical Characteristics (Overall)

Bulk Cable Weight: 1 lbs/1000 ft.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating:	300 V RMS, 80°C
UL Type:	AWM 1061
CSA Rating:	300 V RMS, 80°C
CSA Type:	AWM I, A/B
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
lame Test	
UL Flame Test:	VW-1
CSA Flame Test:	FT1
lenum/Non-Plenum	

Plenum (Y/N): No

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9986 0011000	1,000 FT	2.000 LB	BROWN	Р	28 STR PVC BRN
9986 002100	100 FT	0.200 LB	RED		28 STR PVC RED
9986 0021000	1,000 FT	2.000 LB	RED	Р	28 STR PVC RED
9986 003100	100 FT	0.200 LB	ORANGE		28 STR PVC ORG
9986 0031000	1,000 FT	2.000 LB	ORANGE	Р	28 STR PVC ORG

Page 1 of 2

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



9986 Hook-up/Lead - UL AWM Style 1061

9986 0041000	1,000 FT	2.000 LB	YELLOW	P	28 STR PVC YEL
9986 0051000	1,000 FT	2.000 LB	GREEN, DARK	Р	28 STR PVC GRN
9986 0071000	1,000 FT	2.000 LB	VIOLET	Р	#28 STR PVC VIO
9986 0081000	1,000 FT	2.000 LB	GRAY	Р	28 STR PVC GRY
9986 009100	100 FT	0.200 LB	WHITE		28 STR PVC WHT
9986 0091000	1,000 FT	2.000 LB	WHITE	Р	28 STR PVC WHT
9986 010100	100 FT	0.200 LB	BLACK		28 STR PVC BLK
9986 0101000	1,000 FT	2.000 LB	BLACK	Р	28 STR PVC BLK
9986 0131000	1,000 FT	2.000 LB	BLUE, DARK	Р	28 STR PVC DBLU

Notes:

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 1 Revision Date: 08-16-2013

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sales belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Page 2 of 2